



## COLOSSAL CARNAGE 100 RULES

**Update: NO EXTERNAL MIRROR ALLOWED. STOCK INTERIOR MIRROR ONLY ALLOWED IN STOCK POSITION ON WINDSHIELD.**

1: ANY 4 OR 6 CYLINDER American or foreign street car, mini-van or mini-truck allowed: All 6 cylinder cars must be front wheel drive. Only four cylinder pickup trucks allowed. No 4 wheel drives or all wheel drives allowed. No t-tops allowed. Sunroof must be removed and covered with minimum 22-gauge steel on top and bottom of opening. Car numbers must measure a minimum of 3 feet tall. Numbers will be assigned first come, first serve basis.

\*EVERY car must provide their own scorer! Please bring pencils & clipboards. Clipboards should have your car # on back.\*

2: Cars must be completely stock. Removal of upholstery allowed. All body panels must remain as manufactured. All doors must be welded or chained shut.

3: Front and rear bumpers must be chained or cable to prevent dragging.

4: No anti-freeze allowed. Water is the only allowed engine coolant. It will be checked.

5: Suspension – No modifications allowed. All parts must be stock for make and model. No spacers. No reinforcing, cutting, heating or bending of any suspension front or rearends components allowed. Front Camber limited to stock adjustments not to exceed 1 inch maximum. No racing or performance parts allowed. **NO** rear camber allowed.

6: Tires – All tires must be exact same size, numbers and letters, and tire rating. Must be stock passenger DOT tires only. 60, 65, 70, or 75 series only. No bias ply tires or retread tires are allowed. Directional tires allowed. All tires must have a readable tread wear numerically of 360 or higher and painted white.

7: Wheels – Must be OEM stock wheels. No aftermarket wheels allowed. One-inch lug nuts suggested on right front.

8: Engine – Must be stock for make and model. Stock carb throttle body or fuel injection only. Stock fuel pump only. No after-market fuel systems allowed. Battery must remain in stock location and be secured and covered.

9: Transmission and Driveline – Must be stocked for make and model. No lock or posi-trac differentials.

10: Gas tank must be original stock position or secured in center of trunk. Fuel cell or boat tank secured in trunk.

11: Exhaust must extend to rear-seat area and secured to ground. No exhaust may exit outside of the car.

12: Driver protection roll bars are optional but 4 point cage highly recommend. No outside bars. Roll bars or cage must be professionally welded but not through the firewall. Rear bars may extend to rear strut towers for safety.

**13: All doors must be welded or chained shut. Hood and trunk latches must be removed. Pull-pin hood pins must be used.**

**14: All glass lights in trim chrome and plastic must be removed. Full-front windshield mandatory. (Lexan is allowed) No badly cracked windshield allowed. Full screen is also legal with driver shield or goggles.**

**15: Driver seat with seatbelt in shoulder strap required. Three-point harness recommend. All carpet and upholstery must be removed. All cars must have a fully charged fire extinguisher mounted within drivers reach.**

**16: Safety Equipment – Helmet with a minimum Snell 90 rating. Long pants and sleeves required. Driving suit and driving gloves recommended. Must have driver's side window net mounted at bottom with quick release on top.**